



Hawai'i

Statewide Assessment Program



Secure Browser Installation Manual

For Technology Coordinators

2018-2019

Published July 30, 2018

Prepared by the American Institutes for Research®



Descriptions of the operation of the Test Information Distribution Engine, Test Delivery System, and related systems are property of the American Institutes for Research (AIR) and are used with the permission of AIR.

Table of Contents

Section I. Introduction to the Secure Browser Manual	1
Scope.....	1
System Requirements	1
Manual Content	1
Intended Audience.....	2
Document Conventions	2
Other Resources.....	2
Section II. Installing the Secure Browser on Desktops and Laptops	4
Installing the Secure Browser on Windows	4
Installing the Secure Browser on an Individual Computer	4
Installing the Secure Browser via Windows	4
Installing the Secure Browser via the Command Line	6
Sharing the Secure Browser over a Network	7
Copying the Secure Browser Installation Directory to Testing Computers	8
Installing the Secure Browser for Use with an NComputing Terminal	9
Installing the Secure Browser on a Terminal Server or Windows Server	10
Installing the Secure Browser Without Administrator Rights	12
Uninstalling the Secure Browser on Windows.....	12
Uninstalling via the User Interface	12
Uninstalling via the Command Line	12
Microsoft Take a Test App.....	13
Creating a Dedicated Test Account for Non-permissive Mode Users	13
Creating Desktop Shortcuts for Permissive Mode Users.....	14
Installing the Secure Browser on Mac	15
Installing the Secure Browser on an Individual Mac	15
Cloning the Secure Browser Installation to Other Macs.....	16
Uninstalling the Secure Browser on Mac	16
Installing the Secure Browser on Linux	16
Installing the Secure Browser on 32- or 64-Bit Distributions.....	17
Extracting the Secure Browser TAR File.....	18
Creating a Shortcut to Secure Browser 10.....	18
Uninstalling the Secure Browser on Linux.....	19
Section III. Installing the Secure Browser on Mobile Devices.....	20
Installing the Secure Browser on iOS.....	20
Guidance on iOS Classroom App and Summative Testing	21

Using MDM to Disable Classroom Observation	21
Installing AIRSecureTest on Android.....	22
Installing AirSecureTest on Chrome OS.....	23
Installing AIRSecureTest as a Kiosk App on Standalone Chromebooks.....	23
Installing AIRSecureTest as a Kiosk App on Managed Chromebooks	27
Configuring Your State and Assessment Program on Mobile Devices	29
Installing the Secure Browser on Windows Mobile Devices.....	29
Section IV. Proxy Settings for Desktop Secure Browsers.....	30
Specifying a Proxy Server to Use with the Secure Browser.....	30
Appendix A. Creating Group Policy Objects.....	32
Appendix B. Resetting Secure Browser Profiles.....	34
Resetting Secure Browser Profiles on Windows	34
Resetting Secure Browser Profiles on Mac.....	35
Resetting Secure Browser Profiles on Linux	36
Appendix C. User Support	37
Appendix D. Change Log	38

Table of Figures

Figure 1. Contents of HISecureBrowser-OSX.dmg	15
Figure 2. AIRSecureTest Download Page on the Apple Store	20
Figure 3. AIRSecureTest Download Page on Google Play	22
Figure 4. Chrome OS Missing Message	24
Figure 5. Turn OS Verification Off Message	24
Figure 6. OS Verification Off Message	25
Figure 7. Preparing for Developer Mode Message	25
Figure 8. Welcome Screen.....	25
Figure 9. Join WiFi Network Screen	25
Figure 10. Sign in Screen.....	26
Figure 11. Automatic Kiosk Mode Message	26
Figure 12. Extensions Screen	26
Figure 13. Manage Kiosk Applications Screen	27
Figure 14. Kiosk Apps Window	28
Figure 15. AIRSecureTest Launchpad.....	29
Figure 16. Local Group Policy Editor	32
Figure 17. Logon Properties Dialog Box	33
Figure 18. Add a Script Dialog Box.....	33
Figure 19. Cleaning Secure Browser on Mac	35

Table of Tables

Table 1. Document conventions	2
Table 2. Specifying proxy settings using the command line	31

Section I. Introduction to the Secure Browser Manual

The Secure Browser is a web browser for taking online assessments. The Secure Browser prevents students from accessing other computer or Internet applications and from copying test information. It also occupies the entire computer screen. An updated secure browser must be downloaded and installed onto all testing devices prior to the start of testing in each new school year.

Scope

This manual provides instructions for installing the Secure Browsers on computers and devices used for online assessments.

System Requirements

For the Secure Browser to work correctly, the computer on which you install it must have a supported operating system. For a list of supported operating systems, see the [System Requirements for Online Testing](#) available from the in the [Technology Coordinators](#) section in the Hawaii Statewide Assessment Program portal at <https://www.alohahsap.org>.

Manual Content

This manual is organized as follows:

- [Section I, Introduction to the Secure Browser Manual](#) (this section), describes this guide.
- [Section II, Installing the Secure Browser on Desktops and Laptops](#), includes instructions for installing the Secure Browser onto supported Windows, Mac, and Linux platforms.
- [Section III, Installing the Secure Browser on Mobile Devices](#), includes instructions for installing the mobile Secure Browser onto supported iOS, Android, and Chrome OS platforms.
- [Section IV, Proxy Settings for Desktop Secure Browsers](#), provides commands for specifying proxy servers that the Secure Browser should use.
- [Appendix A, Creating Group Policy Objects](#), describes how to create scripts that launch when a user logs into a Windows computer.
- [Appendix B, Resetting Secure Browser Profiles](#), provides instructions for resetting Secure Browser profiles.
- [Appendix C, User Support](#), provides Help Desk information.

Intended Audience




This installation guide is intended for the following audiences:

- Technology coordinators familiar with downloading installation packages from the Internet or from a network location and installing software onto Windows, Mac, or Linux operating systems or Chromebook, iPad, or Android devices.
- Network administrators familiar with mapping or mounting network drives, and creating and running scripts at the user and host level.
- If you install and run the Secure Browser from an NComputing server, you should be familiar with operating that software and related hardware.

Document Conventions

[Table 1](#) lists typographical conventions and key symbols.

Table 1. Document conventions

Element	Description
	Warning: This symbol accompanies important information regarding actions that may cause fatal errors.
	Alert: This symbol accompanies important information regarding a task that may cause minor errors.
	Tip: This symbol accompanies useful information on how to perform a task.
filename	Monospaced text indicates a directory, filename, or something you enter in a field.
text	Bold text indicates a link or button that is clickable.

Other Resources

- For information about supported operating systems and web browsers, see the [System Requirements for Online Testing](#).
- For information about securing a computer before a test session, see the [Guide to Navigating the Online HSAP Administration](#).
- For information about network and Internet requirements, general peripheral and software requirements, and configuring text-to-speech settings, see the [Technical Specifications Manual for Online Testing](#).

- For information about supported hardware and software for Braille testing as well as information about configuring JAWS, see the [Braille Requirements and Testing Manual](#).
- The above resources, as well as secure browsers and user guides for other systems, are available on the Hawaii Statewide Assessment Program portal (<https://www.alohahsap.org>).

Section II. Installing the Secure Browser on Desktops and Laptops

This section contains installation instructions for Windows, Mac, and Linux under a variety of deployment scenarios. Some scenarios describe installing the Secure Browser on a shared network drive, from which students would then run the Browser. However, there are significant drawbacks in this method. Running the Secure Browser from a shared network drive creates contention among the students' client machines for two resources: LAN bandwidth and shared drive I/O. This performance impact can be avoided by installing the Secure Browser locally on each machine. **AIR strongly discourages the use of network shared drive installation for the Secure Browser, as this setup can compromise the stability and performance of the browser, especially during peak testing times.**

Installing the Secure Browser on Windows

This section provides instructions for installing the [Secure Browser](#) on computers running on 7, 8.0, 8.1, and 10. (The secure browser does not run on other versions of Windows.)

The instructions in this section assume machines are running a 64-bit version of Windows and that the Secure Browser will be installed to C:\Program Files (x86)\. If you are running a 32-bit version of Windows, adjust the installation path to C:\Program Files\.



TIP. If you are testing on Windows 10, consider using the Take a Test app. See the section "[Microsoft Take a Test App](#)" for details.

Installing the Secure Browser on an Individual Computer

This section contains instructions for installing the Secure Browser on individual computers.

Installing the Secure Browser via Windows

In this scenario, a user with administrator rights installs the Secure Browser using standard Windows. (If you do not have administrator rights, refer to the section [Installing the Secure Browser Without Administrator Rights](#).)

1. If you installed a previous version of the Secure Browser by copying its directory from one computer to another, manually uninstall the Secure Browser by deleting the installation folder and the desktop shortcut. (If you installed the Secure Browser using the Windows installation program, the installation package automatically removes it.) See the instructions in the section [Uninstalling the Secure Browser on Windows](#).
2. Navigate to the [Secure Browsers](#) page of the Hawaii Statewide Assessment Program portal at <https://www.alohahsap.org>. Under **Secure Browser**, click the **Windows** tab, then click **Download Browser**. A dialog window opens.

3. Do one of the following (this step may vary depending on the browser you are using):
 - If presented with a choice to **Run** or **Save** the file, click **Run**. This opens the Secure Browser Setup wizard.
 - If presented only with the option to **Save**, save the file to a convenient location. After saving the file, double-click the installation file `HISecureBrowser-Win.msi` to open the setup wizard.
4. Follow the instructions in the setup wizard. When prompted for setup type, click **Install**.
5. Click **Finish** to exit the setup wizard. The following items are installed:
 - The Secure Browser to the default location `C:\Program Files (x86)\HISecureBrowser\ (64-bit)` or `C:\Program Files\HISecureBrowser\ (32-bit)`.
 - A shortcut `HISecureBrowser` to the desktop.
6. Ensure all background jobs, such as virus scans or software updates, are scheduled outside of test windows. For example, if your testing takes place between 8:00 a.m. and 3:00 p.m., schedule background jobs outside of these hours.
7. *Optional:* Apply proxy settings by doing the following:
 - a. Right-click the shortcut `HISecureBrowser` on the desktop, and select **Properties**.
 - b. Under the **Shortcut** tab, in the **Target** field, modify the command to specify the proxy. See [Table 2](#) for available forms of this command.
 - c. Click **OK** to close the Properties dialog box.

For more information about proxy settings, see [Section IV, Proxy Settings for Desktop Secure Browsers](#).
8. Run the browser by double-clicking the `HISecureBrowser` shortcut on the desktop. The Secure Browser opens displaying the student login screen. The browser fills the entire screen and hides the task bar.
9. To exit the browser, click **CLOSE SECURE BROWSER** in the upper-right corner of the screen.

Installing the Secure Browser via the Command Line

In this scenario, a user with administrator rights installs the Secure Browser from the command line. If you do not have administrator rights, refer to the section [Installing the Secure Browser Without Administrator Rights](#).

1. If you are not signed on to the computer as an administrator, obtain the administrator password.
2. If you installed a previous version of the Secure Browser by copying its directory from one computer to another, manually uninstall the Secure Browser by deleting the installation folder and the desktop shortcut. (If you installed the Secure Browser using the Windows installation program, the installation package automatically removes it.) See the instructions in the section [Uninstalling the Secure Browser on Windows](#).
3. Navigate to the [Secure Browsers](#) page of the Hawaii Statewide Assessment Program portal at <https://www.alohahsap.org>. Under **Secure Browser**, click the **Windows** tab, then click **Download Browser**. A dialog window opens.
4. Save the file on the computer (this step may vary depending on the browser you are using):
 - If presented with a choice to **Run** or **Save** the file, click **Save**, and save the file to a convenient location.
 - If presented only with the option to **Save**, save the file to a convenient location.
5. Note the full path and filename of the downloaded file, such as
c:\temp\HISecureBrowser-Win.msi.
6. Open a command prompt as the administrator by doing the following:
 - a. Click **Start**, and locate the Command Prompt application. (In some versions of Windows the application is under **All Programs > Accessories > Command Prompt**.)
 - b. Right-click **Command Prompt**, and select **Run as Administrator**.
 - c. As necessary, type the administrator password for the computer. The command prompt opens.

(You need to do step 6 only once for the current login. The next time you open the command prompt, Windows retains the administrator role.)

7. Run the command `msiexec /I <Source> [/quiet] [INSTALLDIR=<Target>]`

<Source>	Path to the installation file, such as <code>C:\temp\HISecureBrowser-Win.msi</code> .
<Target>	Path to the location where you want to install the Secure Browser. If absent, installs to the directory described in step 9. The installation program creates the directory if it does not exist.
/I	Perform an install.
[/quiet]	Quiet mode, no interaction.

For example, the command

```
msiexec /I c:\temp\HISecureBrowser-Win.msi /quiet  
INSTALLDIR=C:\AssessmentTesting\BrowserInstallDirectory
```

installs the Secure Browser from the installation package at `C:\temp\HISecureBrowser-Win.msi` into the directory `C:\AssessmentTesting\BrowserInstallDirectory` using quiet mode.

8. Follow the instructions in the setup wizard. When prompted for setup type, click **Install**.
9. Click **Finish** to exit the setup wizard. The following items are installed:
 - o The Secure Browser to the default location `C:\Program Files (x86)\HISecureBrowser\ (64-bit)` or `C:\Program Files\HISecureBrowser\ (32-bit)`.
 - o A shortcut `HISecureBrowser` to the desktop.
10. Ensure all background jobs, such as virus scans or software updates, are scheduled outside of test windows. For example, if your testing takes place between 8:00 a.m. and 3:00 p.m., schedule background jobs outside of these hours.
11. Run the browser by double-clicking the `HISecureBrowser` shortcut on the desktop. The Secure Browser opens displaying the student login screen. The browser fills the entire screen and hides the task bar.
12. To exit the browser, click **CLOSE SECURE BROWSER** in the upper-right corner of the screen.

Sharing the Secure Browser over a Network

In this scenario, you install the Secure Browser on a server's shared drive, and you also create a shortcut to the Secure Browser's executable on each testing computer's desktop. This assumes that all testing computers have access to the shared drive. As stated above, **AIR strongly discourages the use of network shared drive installation for the Secure Browser, as this setup**

can compromise the stability and performance of the browser, especially during peak testing times.

1. On the remote computer from which the students run the Secure Browser, install the Secure Browser following the directions in the section [Installing the Secure Browser on an Individual Computer](#).
2. On each testing machine, sign in and do the following:
 - a. Ensure all background jobs, such as virus scans or software updates, are scheduled outside of test windows. For example, if your scheduled testing takes place between 8:00 a.m. and 3:00 p.m., schedule background jobs outside of these hours.
 - b. Copy the desktop shortcut HISecureBrowser from the remote machine to the directory C:\Users\Public\Public Desktop.
 - c. Run the browser by double-clicking the HISecureBrowser shortcut on the desktop. The Secure Browser opens displaying the student login screen. The browser fills the entire screen and hides the task bar.
 - d. To exit the browser, click **CLOSE SECURE BROWSER** in the upper-right corner of the screen.

Copying the Secure Browser Installation Directory to Testing Computers

In this scenario, a network administrator installs the Secure Browser on one machine, and copies the entire installation directory to testing computers.

1. On the computer from where you will copy the installation directory, install the Secure Browser following the directions in the section [Installing the Secure Browser on an Individual Computer](#). Note the path of the installation directory, such as C:\Program Files (x86)\HISecureBrowser.
2. Identify the directory on the local testing computers to which you will copy the browser file (it should be the same directory on all computers). For example, you may want to copy the directory to c:\AssessmentTesting\. Ensure you select a directory in which the students can run executables.
3. On each local testing computer, do the following:
 - a. Ensure all background jobs, such as virus scans or software updates, are scheduled outside of test windows. For example, if your scheduled testing takes place between 8:00 a.m. and 3:00 p.m., schedule background jobs outside of these hours.

- b. Copy the installation directory used in step [1](#) from the remote machine to the directory you selected in step [2](#). For example, if the target directory is c:\AssessmentTesting\, you are creating a new folder c:\AssessmentTesting\HISecureBrowser.
- c. Copy the shortcut c:\AssessmentTesting\HISecureBrowser\HISecureBrowser.exe - Shortcut.lnk to the desktop.
- d. Run the browser by double-clicking the HISecureBrowser shortcut on the desktop. The Secure Browser opens displaying the student login screen. The browser fills the entire screen and hides the task bar.
- e. To exit the browser, click **CLOSE SECURE BROWSER** in the upper-right corner of the screen.

Installing the Secure Browser for Use with an NComputing Terminal

In this scenario, a network administrator installs the Secure Browser on a Windows server accessed through an NComputing terminal. Prior to testing day, the testing coordinator connects consoles to the NComputing terminal, logs in from each to the Windows server, and starts the Secure Browser so that it is ready for the students.

This procedure assumes that you already have a working NComputing topology with consoles able to reach the Windows server.

For a listing of supported terminals and servers for this scenario, see [System Requirements for Online Testing](#), available from the Hawaii Statewide Assessment Program portal (<https://www.alohahsap.org>).

1. Log in to the machine running the Windows server.
2. Install the Secure Browser following the directions in the section [Installing the Secure Browser on an Individual Computer](#).
3. Open Notepad and type the following command (no line breaks):

```
"C:\Program Files (x86)\HISecureBrowser\HISecureBrowser.exe" -CreateProfile %SESSIONNAME%
```

If you used a different installation path on the Windows server, use that in the above command.

4. Save the file to the desktop as logon.bat.
5. Create a group policy object that runs the file logon.bat each time a user logs in. For details, see [Appendix A, Creating Group Policy Objects](#).

6. On each NComputing console, create a new HISecureBrowser desktop shortcut by doing the following (this step is necessary because the default shortcut created by the installation program has an incorrect target):
 - a. Connect to the NComputing terminal.
 - b. Log in to the Windows server with administrator privileges.
 - c. Delete the Secure Browser's shortcut appearing on the desktop.
 - d. Navigate to the Secure Browser's installation directory, usually C:\Program Files (x86)\HISecureBrowser\.
 - e. Right-click the file HISecureBrowser.exe and select **Send To > Desktop (create shortcut)**.
 - f. On the desktop, right-click the new shortcut and select **Properties**. The Shortcut Properties dialog box appears.
 - g. Under the **Shortcut** tab, in the **Target** field, type the following command:

```
"C:\Program Files(X86)\HISecureBrowser\HISecureBrowser.exe" -P%SESSIONNAME%
```

If you used a different installation path on the Windows server, use that in the above command.
 - h. Click **OK** to close the Properties dialog box.
7. Verify the installation by double-clicking the shortcut to start the Secure Browser.

Installing the Secure Browser on a Terminal Server or Windows Server

In this scenario, a network administrator installs the Secure Browser on a server—either a terminal server or a Windows server. Testing machines then connect to the server's desktop and run the Secure Browser remotely. This scenario is supported on Windows Server 2008 R2, 2012 R2, and 2016 R2.



CAUTION: Testing Quality with Servers Launching a Secure Browser from a terminal or Windows server is typically not a secure test environment, because students can use their local machines to search for answers. Therefore, AIR does not recommend this installation scenario for testing.

1. Log in to the server, and install the Secure Browser by following the directions in the section [Installing the Secure Browser on an Individual Computer](#). Note the path of the installation directory.

2. Copy and paste the line below into Notepad (no line breaks):

```
"C:\Program Files (x86)\HISecureBrowser\HISecureBrowser" -CreateProfile  
%SESSIONNAME%
```

If you used a different installation path, use that in the above command.

3. Save the file to the desktop as `logon.bat`.
4. Create a group policy object that runs the file `logon.bat` each time a user connects to the server's desktop. For details, see [Appendix A, Creating Group Policy Objects](#).
5. On each client, create a new `HISecureBrowser` desktop shortcut by doing the following (this step is necessary because the default shortcut created by the installation program has an incorrect target):
 - a. Connect from the client to the server.
 - b. On the desktop provided by the server, delete the Secure Browser's shortcut.
 - c. Navigate to the Secure Browser's installation directory, usually `C:\Program Files (x86)\HISecureBrowser\`.
 - d. Right-click the file `HISecureBrowser.exe` and select **Send To > Desktop (create shortcut)**.
 - e. On the desktop, right-click the new shortcut and select **Properties**. The Shortcut Properties dialog box appears.
 - f. Under the **Shortcut** tab, in the **Target** field, type the following command:

```
"C:\Program Files(X86)\HISecureBrowser\HISecureBrowser.exe" -P%SESSIONNAME%
```

If you used a different installation path on the server, use that in the above command.
 - g. Click **OK** to close the Properties dialog box.
6. Verify the installation by double-clicking the shortcut to start the Secure Browser.

Installing the Secure Browser Without Administrator Rights

In this scenario, you copy the Secure Browser from one machine where it is installed onto another machine on which you do not have administrator rights.

1. Log on to a machine on which the Secure Browser is installed.
2. Copy the entire folder where the browser was installed (usually `C:\Program Files (x86)\HISecureBrowser`) to a removable drive or shared network location.
3. Copy the entire directory from the shared location or removable drive to any directory on the target computer.
4. In the folder where you copied the Secure Browser, right-click `HISecureBrowser.exe` and select **Send To > Desktop (create shortcut)**.
5. Ensure all background jobs, such as virus scans or software updates, are scheduled outside of test windows. For example, if your testing takes place between 8:00 a.m. and 3:00 p.m., schedule background jobs outside of these hours.
6. Double-click the desktop shortcut to run the Secure Browser.

Uninstalling the Secure Browser on Windows

The following sections describe how to uninstall the Secure Browser from Windows or from the command line.

Uninstalling via the User Interface

The following instructions may vary depending on your version of Windows.

1. Navigate to **Settings > System > Apps & features** (Windows 10) or **Control Panel > Add or Remove Programs** or **Uninstall a Program** (previous versions of Windows).
2. Select the Secure Browser program `HISecureBrowser` and click **Remove** or **Uninstall**.
3. Follow the instructions in the uninstall wizard.

Uninstalling via the Command Line

1. Open a command prompt.
2. Run the command `msiexec /X <Source> /quiet`

`<Source>` Path to the executable file, such as `C:\MSI\HISecureBrowser.exe`.

`/X` Perform an uninstall.

`[/quiet]` Quiet mode, no interaction.

For example, the command

```
msiexec /X C:\AssessmentTesting\HISecureBrowser.exe /quiet
```

uninstalls the Secure Browser installed at C:\AssessmentTesting\ using quiet mode.

Microsoft Take a Test App

Windows 10 comes with Microsoft's Take a Test app, which enforces a locked-down, secure testing environment identical to AIR's Secure Browser. Users of the Take a Test app do not need to install the AIR Secure Browser on the testing machine. For more information about configuring Take a Test, see <https://docs.microsoft.com/en-us/education/windows/take-tests-in-windows-10>.

Creating a Dedicated Test Account for Non-permissive Mode Users

Non-permissive mode users should create a dedicated test account for the Take a Test app. Permissive mode features will not be available when using this method. To access permissive mode features, please see [Creating Desktop Shortcuts for Permissive Mode Users](#).



Note: Assessments administered through the Take a Test app will detect some forbidden apps are running in the background even if users don't start these apps, which causes the Take a Test app to log a user out of their account. (For more information, see <https://support.microsoft.com/en-us/help/4338725/k-12-assessment-unexpected-reports-apps-running-background-windows-10>) Because of this, AIR has disabled the forbidden app check when using the Take a Test app through a dedicated test account which blocks access to opening these apps by default.

To create a dedicated test account:

1. Sign into the device with an administrator account.
2. Go to **Settings > Accounts > Work or school Access > Set up an account for taking tests**.
3. Select an existing account to use as the dedicated testing account.



Note: If you don't have an account on the device, you can create a new account. To do this, go to **Settings > Accounts > Family & Other Users > Add someone else to this PC > I don't have this person's sign-in information > Add a user without a Microsoft account**.

4. In the *Enter the test's web address* field, enter <https://hi.tds.airast.org/student>
5. Click **Save**.


The student can now sign in to the dedicated account to take the specified test.

Creating Desktop Shortcuts for Permissive Mode Users

Permissive mode users should create a desktop shortcut for the Take a Test app.

To create a desktop shortcut for Take a Test:

1. Log in to Windows as the user taking a test.
2. Right-click on the desktop and select **New > Shortcut**. The Create Shortcut dialog box appears.



3. In the *Type the location of the item* field, enter
`ms-edu-secureassessment:https://hi.tds.airast.org/student`
4. Click **Next**.
5. In the next dialog box, type a name for the shortcut.
6. Click **Finish**.

The shortcut appears on the desktop. To run the Take a Test app, double-click the shortcut. To exit the Take a Test app, press **Ctrl+Atl+Del**.

Installing the Secure Browser on Mac

This section provides instructions for installing the [secure browsers](#) on Macintosh desktop and laptop computers.

Installing the Secure Browser on an Individual Mac

In this scenario, a user installs the Secure Browser on desktop or laptop computers running Mac OS. The steps in this procedure may vary depending on your version of Mac OS and your web browser.

1. Remove any previous versions of the Secure Browser by dragging its folder to the Trash.
2. Navigate to the [Secure Browser](#) page of the Hawaii Statewide Assessment Program portal at <https://www.alohahsap.org>. Click the **Mac** tab, then click **Download Browser**. If prompted for a download location, select your downloads folder.
3. Open Downloads from the Dock, and click HISecureBrowser-OSX.dmg to display its contents (see [Figure 1](#)).

Figure 1. Contents of HISecureBrowser-OSX.dmg



4. Drag the HISecureBrowser icon to the folder. This installs the Secure Browser into Applications.
5. Ensure all background jobs, such as virus scans or software updates, are scheduled outside of test windows. For example, if your testing takes place between 8:00 a.m. and 3:00 p.m., schedule background jobs outside of these hours.
6. Disable Mission Control/Spaces. Instructions for disabling Spaces are in the [Technical Specifications Manual for Online Testing](#), available from the Hawaii Statewide Assessment Program portal (<https://www.alohahsap.org>).

7. In Finder, navigate to **Go > Applications**, and double-click **HISecureBrowser** to launch the Secure Browser. (You must launch the Secure Browser to complete the installation.) The Secure Browser opens displaying the student login screen. The browser fills the entire screen and hides the dock.
8. To exit the browser, click **CLOSE SECURE BROWSER** in the upper-right corner of the screen.
9. Create a desktop shortcut; from the **Applications** folder, drag HISecureBrowser to the desktop.

Cloning the Secure Browser Installation to Other Macs

Depending on your networking and permissions, it may be faster to install the Secure Browser onto a single Mac, take an image of the disk, and copy the image to other Macs.

To clone the Secure Browser installation to other computers:

1. On the computer from where you will clone the installation, do the following:
 - a. Install the Secure Browser following the directions in the section [Installing the Secure Browser on an Individual Mac](#). Be sure to run and then close the Secure Browser after the installation.
 - b. In Finder, display the **Library** folder.
 - c. Open the **Application Support** folder. See [Figure 19](#).
 - d. Delete the folder containing the Secure Browser.
 - e. Delete the Mozilla folder.
2. Create a shell script that creates a new Secure Browser profile when a user logs in. The basic command to create a profile is `<install_directory>/Contents/MacOS/HISecureBrowser --CreateProfile profile_name`, where `profile_name` is unique among all testing computers.
3. Clone the image.
4. Deploy the image to the target Macs.

Uninstalling the Secure Browser on Mac

To uninstall a Mac Secure Browser, drag its folder to the Trash.

Installing the Secure Browser on Linux

This section provides instructions for installing the [Secure Browser](#) on computers running a supported Linux distribution. For more information about Linux requirements, refer to the

[Technical Specifications Manual for Online Testing](#), available from the Hawaii Statewide Assessment Program portal (<https://www.alohahsap.org>).

Installing the Secure Browser on 32- or 64-Bit Distributions

There are two versions of the Secure Browser: one for 32-bits and another for 64-bits. These installation instructions may vary for your individual Linux distribution.

1. Uninstall any previous versions of the Secure Browser by deleting the directory containing it.
2. Obtain the root or super-user password for the computer on which you are installing the Secure Browser.
3. Navigate to the [Secure Browser](#) page of the Hawaii Statewide Assessment Program portal at <https://www.alohahsap.org>. Click the **Linux** tab for your distribution (32-bit or 64-bit), then click **Download Browser**. Save the file to the desktop.
4. Right-click the downloaded file `HISecureBrowserX.X-YYYY-MM-DD-i686.tar.bz2` (32-bit) or `HISecureBrowserX.X-YYYY-MM-DD-x86_64.tar.bz2` (64-bit), and select **Extract Here** to expand the file. This creates the `HISecureBrowser` folder on the desktop.
5. In a file manager, open the `HISecureBrowser` folder.
6. For Ubuntu, disable automatic running of scripts by doing the following (otherwise skip to step 7)
 - a. From the menu bar, select **Edit > Preferences**. On the **Behavior** tab, mark the **Ask each time** radio button.
 - b. Click **Close**.
7. Change the installation script to executable by doing the following:
 - a. Right-click the file `install-icon.sh`, and select **Properties**.
 - b. On the **Permissions** tab, mark the **Allow executing file as a program** checkbox.
 - c. Click **Close**.
8. Double-click the file `install-icon.sh`. In the next dialog box, click **Run in Terminal**. The installation script prompts you for the root or super-user password you obtained in step 2.
9. Enter the password. The script installs all dependent libraries and supported voice packs, and creates a `HISecureBrowser` icon on the desktop.

10. Ensure all background jobs, such as virus scans or software updates, are scheduled outside of test windows. For example, if your testing takes place between 8:00 a.m. and 3:00 p.m., schedule background jobs outside of these hours.
11. If text-to-speech testing is performed on this computer, reboot it.
12. From the desktop, double-click the HISecureBrowser icon to launch the browser. An **Untrusted App Launcher** error message appears.
13. Click **Trust and Launch**. The student login screen appears. The browser fills the entire screen and hides any panels or launchers.
14. To exit the browser, click **CLOSE SECURE BROWSER** in the upper-right corner of the screen.

Extracting the Secure Browser TAR File

Users attempting to install the Secure Browser on Fedora 27-28 or Ubuntu 18.04 have been encountering an issue where the Secure Browser extracts to the **Home** folder and not the **Desktop** folder. This is a feature in these operating systems. This is not an error in the Secure Browser. The following procedure explains how to extract the Secure Browser TAR file manually using terminal commands.

To extract the Secure Browser manually using terminal commands:

1. Launch **Terminal**.
2. Type **tar xfv [Secure Browser File Name].tar.bz2**.
3. Press **Enter**.

Creating a Shortcut to Secure Browser 10

Installation of Secure Browser 10 on machines running Fedora or Ubuntu Linux will not automatically install a shortcut to the browser. Users must manually create a shortcut. The following procedure explains how to complete this process.

To manually create a shortcut to the Secure Browser in Fedora or Ubuntu Linux:

1. Open **Terminal**.
2. Type **cd /location of Secure Browser/**
3. Type **./install-icon.sh**
4. Press **Enter**.
5. Close **Terminal**.

6. Open Secure Browser folder.
7. Click **install-icon.sh**.

Note: A window displaying “Do you want to run install-icon.sh or display its contents?” will appear.

8. Click **Run**.

Uninstalling the Secure Browser on Linux

To uninstall a Secure Browser, delete the directory containing it.

Section III. Installing the Secure Browser on Mobile Devices

This section contains information about installing AIRSecureTest, the Secure Browser app for iOS, Android, and Chrome OS. For information about configuring supported tablets and Chromebooks to work with the Secure Browser, refer to the [Technical Specifications Manual for Online Testing](#), available from the Hawaii Statewide Assessment Program portal (<https://www.alohahsap.org>).


Installing the Secure Browser on iOS

This section contains instructions for downloading and installing AIRSecureTest and selecting your state and assessment program. The process for installing the Secure Browser is the same as for any other iOS application. (To install the Secure Browser on many iOS devices simultaneously, consider using Autonomous Single App Mode. For details, see the section “Configuring Using Autonomous Single App Mode” in [Technical Specifications Manual for Online Testing](#).) (To run the Secure Browser or classroom app in iOS, you must first disable Speech to Text.)

1. On your iPad, navigate to the **Secure Browser** page of the Hawaii Statewide Assessment Program portal at <https://www.alohahsap.org>, and click the iOS tab. Click **Download on the App Store**. (You can also search for AIRSecureTest in the App Store to find the Secure Browser app.) The AIRSecureTest download page opens (see [Figure 2](#)).

Figure 2. AIRSecureTest Download Page on the Apple Store



2. Tap . The iPad downloads and installs the Secure Browser, and the button changes to **Open**. After installation, an AIRSecureTest icon appears on the iPad's home screen.

3. Configure the test administration by following the procedure in the section [Configuring Your State and Assessment Program on Mobile Devices](#).

Guidance on iOS Classroom App and Summative Testing

Classroom allows a teacher or proctor to remotely view and monitor a student's iPad. This feature can be disabled via mobile device management (MDM), by un-installing the Classroom app, or by turning off Bluetooth on the teacher iPad during testing windows.

Using MDM to Disable Classroom Observation

You can use the following key value to disable access to the Classroom observation feature on student devices. This key is defined as part of the Restrictions profile payload and is documented in the [Configuration Profile Reference](#).



Warning: Student monitoring software (such as Hapara, etc.) may not be used during testing. This software may run on the student tablets, such as Chromebooks, when the Secure Browser has been launched in Kiosk mode, but the test coordinator, technology coordinator and/or others who may have access to the parent computer may not use these program(s) during testing. Access to students' screens via student monitoring software during testing is considered to be a test security violation.

allowScreenShot	Boolean	If set to false, users can't save a screenshot of the display and are prevented from capturing a screen recording; it also prevents the Classroom app from observing remote screens. Defaults to true.
-----------------	---------	--


Installing AIRSecureTest on Android

You can download AIRSecureTest from the Hawaii Statewide Assessment Program portal or from the Google Play store. The process for installing the Secure Browser is the same as for any other Android application.

This section contains instructions for downloading and installing AIRSecureTest, setting up a restricted profile, and selecting your state and assessment program.

1. On your Android tablet, navigate to the **Secure Browser** page of the Hawaii Statewide Assessment Program portal at <https://www.alohahsap.org> and tap the Android tab. Tap **Get it on Google play**. (You can also search for AIRSecureTest in the Google Play store to find the Secure Browser app.) The AIRSecureTest download page appears.

Figure 3. AIRSecureTest Download Page on Google Play



2. Tap **Install**, and then tap **Accept**. The tablet downloads and installs the Secure Browser.
3. Open **Settings**.
4. Tap **Cloud and accounts**.
5. Tap **Users**.
6. Tap **Add user or profile**.
7. Tap **Restricted profile**. The new profile opens with a list.
8. Tap **New profile**, enter a name, and tap **OK**.
9. Enable **AIRSecureBrowser** from the list. Users will only have access to the **AIRSecureBrowser** in the restricted profile. All other apps will be disabled.
10. Tap **Back**.
11. Swipe down from the top of the tablet with two fingers. **Quick Settings** will open.
12. Tap **Switch user**.

13. Tap the newly named restricted profile.
14. Tap **AIRSecureBrowser**.
15. Configure the test administration by following the procedure in the section [Configuring Your State and Assessment Program on Mobile Devices](#).

**Android Secure Browser Keyboard**

If the Secure Browser keyboard has not been selected via device settings on Android tablets, it will need to be selected upon opening the AIRSecureTest app.

For more information about the Android Secure Browser keyboard, including instructions for enabling it, refer to the [Technical Specifications Manual for Online Testing](#), available from the Hawaii Statewide Assessment Program portal (<https://www.alohasap.org>), Download Secure Browsers page.

Installing AirSecureTest on Chrome OS

This section contains instructions for installing AIRSecureTest, the Secure Browser app for Chrome OS, as a kiosk application.

**Chromebooks Manufactured in 2017 or later**

Due to recent changes by Google, users with Chromebooks manufactured in 2017 or later who do not have an Enterprise or Education license **will not** be able to use those machines for assessments. Google no longer allows users without these licenses to set up kiosk mode, which is necessary to run the AIR Secure Browser.

This change restricting kiosk mode does not affect the Chrome operating system. You can still use any version of Chrome OS on hardware manufactured in 2016 or earlier.

For information about supported operating systems for testing please see the [System Requirements for Online Testing](#) manual available on alohasap.org.

Installing AIRSecureTest as a Kiosk App on Standalone Chromebooks

These instructions are for installing the AIRSecureTest Secure Browser as a kiosk app on standalone Chromebook devices.



Warning Step 5 of this procedure erases all data on the Chromebook. Before wiping, be sure to back up any data.

1. From your network administrator, obtain the following:
 - The wireless network to which the Chromebook connects. This typically includes the network's SSID, password, and other access credentials.
 - An email and password for logging in to Gmail.
2. Power off, then power on your Chromebook.




3. If the OS verification is off message appears (similar to [Figure 6](#)), do the following (otherwise skip to step [4](#)):
 - a. Press **Space**. In the confirmation screen, press **Enter**. The Chromebook reboots.
 - b. In the Welcome screen (see [Figure 8](#)), select your language, keyboard, and enter the network name and password you obtained in step [1](#). Back in the Welcome screen, click **Continue**.
 - c. In the Google Chrome OS Terms screen, click **Accept and continue**. The Sign in screen appears.
4. If this Chromebook was already wiped and configured for a wireless network, skip to step [10](#); otherwise, continue with step [5](#).
5. In the Sign in screen, wipe the Chromebook by doing the following:
 - a. Press **Esc** +  + . A yellow exclamation mark appears similar to that in [Figure 4](#).

Figure 4. Chrome OS Missing Message




- b. Press **Ctrl + D**. The message in [Figure 5](#) appears.

Figure 5. Turn OS Verification Off Message

To turn OS verification OFF, press Enter.
Your system will reboot and local data will be cleared.
To go back, press ESC.


- c. Press **Enter**. A message similar to that in [Figure 6](#) appears.

Figure 6. OS Verification Off Message




- d. Press **Ctrl + D**. The Chromebook indicates it is transitioning to developer mode (see [Figure 7](#)). The transition takes approximately 10 minutes, after which the Chromebook reboots.

Figure 7. Preparing for Developer Mode Message




- e. After the Chromebook reboots, the OS verification is Off message appears again (see [Figure 6](#)). Press **Space**, then press **Enter**. The Chromebook reboots, and the Welcome screen appears (see [Figure 8](#)).

Figure 8. Welcome Screen



6. In the Welcome screen, select your language, keyboard, and network. The Join WiFi network screen appears (see [Figure 9](#)).


Figure 9. Join WiFi Network Screen



7. Enter the network's password you obtained in step [1](#).


- Click **Connect**, and back in the Welcome screen click **Continue**.
- In the Google Chrome OS Terms screen, click **Accept and continue**. The Sign in screen appears (see [Figure 10](#)).

Figure 10. Sign in Screen



- In the Sign in screen, press **Ctrl + Alt + K**. The Automatic Kiosk Mode screen appears (see [Figure 11](#)).

Figure 11. Automatic Kiosk Mode Message






- Click **Enable**, then click **OK**. The Sign in screen appears (see [Figure 10](#)).
- In the Sign in screen, enter the Gmail address you obtained in step [1](#), click **Next**, enter the password, and click **Next** again.
- When you get to the desktop, click the Chrome icon () to open Chrome.
- In the URL bar, enter `chrome://extensions`. The Extensions screen appears (see [Figure 12](#)).

Figure 12. Extensions Screen



15. Mark the checkbox for **Developer Mode**.
16. Click **Manage kiosk applications** located at the top of the screen. The Manage Kiosk Applications screen appears (see [Figure 13](#)).

Figure 13. Manage Kiosk Applications Screen



17. Do the following in the Manage Kiosk Applications screen:
 - a. Enter the following into the **Add kiosk application** field:
hblfbmjdaalalhifaajnnodlkiloengc
 - b. Click **Add**. The AIRSecureTest application appears in the Manage Kiosk Applications list.
 - c. Click **Done**.
18. Click your avatar in the lower-right corner, and then click **Sign Out**.
19. Back at the desktop, click **Apps** at the bottom of the screen, then click **AIRSecureTest**. The Secure Browser launches.
20. If you receive the following error message, then the Secure Browser is not configured to run in kiosk mode.

The AIRSecureTest application requires kiosk mode to be enabled.

You need to re-install the app in kiosk mode by restarting this procedure.
21. Configure the test administration by following the procedure in the section [Configuring Your State and Assessment Program on Mobile Devices](#).


Installing AIRSecureTest as a Kiosk App on Managed Chromebooks

These instructions are for installing the AIRSecureTest Secure Browser as a kiosk app on domain-managed Chromebook devices. The steps in this procedure assume that your Chromebooks are already managed through the admin console.

AIRSecureTest is not compatible with public sessions.

1. As the Chromebook administrator, log in to your admin console (<https://admin.google.com>).
2. Click **Device management**. The Device management page appears.
3. In the left side of the page, click **Chrome management**, and in the next page click **Device settings**.
4. In the **Device settings** page, scroll down to the *Kiosk Settings* section.
5. Click **Manage Kiosk Applications**. The **Kiosk Apps** window appears (see [Figure 14](#)).

Figure 14. Kiosk Apps Window



6. If any AIRSecureTest apps appear in the right column, remove them by clicking **Remove**.
7. Add the AIRSecureTest app by doing the following:
 - a. Click **Manage Kiosk Applications**. The **Kiosk Apps** window appears.
 - b. Click **Chrome Web Store**.
 - c. In the search box, enter AIRSecureTest and press **Enter**. The AIRSecureTest app appears.
 - d. Click **Add**. The app appears in the *Total to install* section.
 - e. Click **Save**. The AIRSecureTest application appears on all managed Chromebook devices.

Configuring Your State and Assessment Program on Mobile Devices

The first time you open the AIRSecureTest app, a launchpad appears. This launchpad establishes the test administration to which your students will log in.

1. Under **Please Select Your State**, select **Hawaii** from the drop-down list (see [Figure 15](#)).

Figure 15. AIRSecureTest Launchpad



The screenshot shows the AIR Assessment logo in the top left. Below it, there are two main sections. The first section is titled "Please Select Your State / Organization:" and contains a dropdown menu. The second section is titled "Choose Your Assessment Program:" and contains a dropdown menu and an "OK" button.

2. Under **Choose Your Assessment Program**, the Hawaii Statewide Assessment Program should already be selected.
3. Tap or select **OK**. The student login page will load. The Secure Browser is now ready for students to use.

The launchpad appears only once. The student login page appears the next time the Secure Browser is launched.

Installing the Secure Browser on Windows Mobile Devices

The procedure for installing the Secure Browser on Windows mobile devices is the same for installing it on desktops. See the section [Installing the Secure Browser via Windows](#) for details.

Section IV. Proxy Settings for Desktop Secure Browsers

This section describes the commands for passing proxy settings to the Secure Browser, as well as how to implement those commands on the desktop computer.

Specifying a Proxy Server to Use with the Secure Browser

By default, the Secure Browser attempts to detect the settings for your network's web proxy server. However, users of web proxies should execute a proxy command once from the command prompt. This command does not need to be added to the Secure Browser shortcut. [Table 2](#) lists the form of the command for different settings and operating systems. To execute these commands from the command line, change to the directory containing the Secure Browser's executable file.



Note: Domain names in commands

The commands in [Table 2](#) use the domains foo.com and proxy.com. When configuring for a proxy server, use your actual testing domain names as listed in the section "URLs for Testing Sites" in the [Technical Specifications Manual for Online Testing](#).

Table 2. Specifying proxy settings using the command line

Description	System	Command
Use the browser without any proxy	Windows	HISecureBrowser.exe -proxy 0 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Mac	./HISecureBrowser -proxy 0 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Linux	./HISecureBrowser.sh -proxy 0 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
Set the proxy for HTTP requests only	Windows	HISecureBrowser.exe -proxy 1:http:foo.com:80 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Mac	./HISecureBrowser -proxy 1:http:foo.com:80 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Linux	./HISecureBrowser.sh -proxy 1:http:foo.com:80 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
Set the proxy for all protocols to mimic the "Use this proxy server for all protocols" of Firefox	Windows	HISecureBrowser.exe -proxy 1:*:foo.com:80 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Mac	./HISecureBrowser -proxy 1:*:foo.com:80 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Linux	./HISecureBrowser.sh -proxy 1:*:foo.com:80 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
Specify the URL of the PAC file	Windows	HISecureBrowser.exe -proxy 2:proxy.com aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Mac	./HISecureBrowser -proxy 2:proxy.com aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Linux	./HISecureBrowser.sh -proxy 2:proxy.com aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
Auto-detect proxy settings	Windows	HISecureBrowser.exe -proxy 4 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Mac	./HISecureBrowser -proxy 4 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Linux	./HISecureBrowser.sh -proxy 4 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
Use the system proxy setting (default)	Windows	HISecureBrowser.exe -proxy 5 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Mac	./HISecureBrowser -proxy 5 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=
	Linux	./HISecureBrowser.sh -proxy 5 aHR0cHM6Ly9oc2EudGRzLmFpcmFzdC5vcmcvc3R1ZGVudC8=


Appendix A. Creating Group Policy Objects

Many of the procedures in the section [Installing the Secure Browser on Windows](#) refer to creating a group policy object. These are objects that Windows executes upon certain events. The following procedure explains how to create a group policy object that runs a script when a user logs in. The script itself is saved in a file `logon.bat`.

For additional information about creating group policy objects, see “Assign user logon scripts” at [https://technet.microsoft.com/en-us/library/cc754740\(v=ws.11\).aspx](https://technet.microsoft.com/en-us/library/cc754740(v=ws.11).aspx).


1. In the task bar (Windows 10), or in **Start > Run** (previous versions of Windows), enter `gpedit.msc`. The Local Group Policy Editor appears (see [Figure 16](#)).

Figure 16. Local Group Policy Editor




2. Expand **Local Computer Policy > User Configuration > Windows Settings > Scripts (Logon/Logoff)**.
3. Select **Logon** and click **Properties**. The Logon Properties dialog box appears (see [Figure 17](#)).

Figure 17. Logon Properties Dialog Box



4. Click **Add**. The Add a Script dialog box appears ([Figure 18](#)).

Figure 18. Add a Script Dialog Box



5. Click **Browse...**, and navigate to the logon.bat you want to run.
6. Click **OK**. You return to the Logon Properties dialog box.
7. Click **OK**. You return to the Local Group Policy Editor.
8. Close the Local Group Policy Editor.

Appendix B. Resetting Secure Browser Profiles

If the Help Desk advises you to reset the Secure Browser profile, use the instructions in this section.

Resetting Secure Browser Profiles on Windows

The following procedure applies to Windows 7 and later.

1. Log on as an admin user or as the user who installed the Secure Browser, and close any open Secure Browsers.
2. Delete the contents of the following folders:
 - C:\Users\username\AppData\Local\AIR\
 - C:\Users\username\AppData\Roaming\AIR\


where `username` is the Windows user account where the Secure Browser is installed. (Keep the AIR\ folders, just delete their contents.)

3. Start the Secure Browser.

Resetting Secure Browser Profiles on Mac

1. Log on as an admin user or as the user who installed the Secure Browser, and close any open Secure Browsers.
2. Start Finder.
3. While pressing **Option**, select **Go > Library**. The contents of the Library folder appear. See [Figure 19](#).
4. Open the **Application Support** folder, and delete the folder containing the Secure Browser.
5. Returning to the Library, open the **Caches** folder, and delete the Secure Browser's folder.
6. Restart the Secure Browser.

Figure 19. Cleaning Secure Browser on Mac



Delete this folder's contents to reset a secure browser's profile

Resetting Secure Browser Profiles on Linux

1. Log on as a superuser or as the user who installed the Secure Browser, and close any open Secure Browsers.
2. Open a terminal, and delete the contents of the following directories:
 - /home/username/.air
 - /home/username/.cache/air

where `username` is the user account where the Secure Browser is installed. (Keep the directories, just delete their contents.)

3. Restart the Secure Browser.

Appendix C. User Support

If this document does not answer your questions, please contact the Hawaii Statewide Assessment Program Help Desk.

The Help Desk is open Monday–Friday from 7:30 a.m. to 4:00 p.m. HST (except holidays).

Hawaii Statewide Assessment Program Help Desk

Toll-Free Phone Support: 1-866-648-3712

Email Support: hsaphelpdesk@air.org

If you contact the Help Desk, you will be asked to provide as much detail as possible about the issues you encountered. You may choose to use the *Help Desk Intake Form*, available on the alohahsap.org portal website in the **Resources >> Technology** section.

Include the following information:

- Test Administrator name and IT/network contact person and contact information
- SSIDs of affected students
- Results ID for the affected student tests
- Operating system and browser version information
- Any error messages and codes that appeared, if applicable
- Information about your network configuration:
 - Secure Browser installation (to individual machines or network)
 - Wired or wireless Internet network setup

Appendix D. Change Log

This Change Log can be used to identify specific changes that are made to any of the information included in the original document throughout the current school year.

Change	Section	Date